



Sun Control Window Films

Performance Results:

Visible Light Transmitted	16%
Total Solar Energy Rejected	66%
UV Light Rejected	99%
Glare Reduction	82%
Visible Light Reflected	17%
Solar Heat Reduction	59%



Neutral 20

Available at:



A higher standard

www.sunrayfilms.com



RE20NEARL

Neutral 20 Benefits:

- High heat rejection provides energy savings and improved comfort
- Reduces fading and helps to protect furnishings
- Comprehensive 3M manufacturer's warranty
- Reduces glare and eye discomfort
- Increases personal safety from flying glass

Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible Light Transmitted	16%	9%	14%	9%
Total Solar Energy Rejected	66%	68%	51%	64%
UV Light Rejected	99%	99%	99%	99%
Glare Reduction	82%	82%	82%	80%
Visible Light Reflected	17%	8%	21%	11%
Shading Coefficient	0.39	0.37	0.56	0.41
Emissivity	0.84	0.84	0.84	0.84
U Value	1.06	1.06	0.50	0.50
Solar Heat Reduction	59%	46%	31%	25%

Double pane application is not recommended unless approved by a 3M representative.

3M Building and Commercial Services Division

3M Center, Building 223-2N-21
St. Paul, MN 55144-1000

Printed in U.S.A. © 3M 2008 70-0709-0169-2 (48.5)ii



The Skin Cancer Foundation recommends this 3M Window Film product as an effective UV protectant.

For color and appearance on our sample cards, no UV Protection or Abrasion Coating has been applied.