



Sun Control Window Films

Performance Results:

Visible Light Transmitted	33%
Total Solar Energy Rejected	65%
UV Light Rejected	98%
Glare Reduction	63%
Visible Light Reflected	42%
Solar Heat Reduction	57%



Silver 35

Available at:



A higher standard

www.sunrayfilms.com



RE35SIAR

Silver 35 Benefits:

- High heat rejection provides energy savings and improved comfort
- Reduces fading and helps to protect furnishings
- Comprehensive 3M manufacturer's warranty
- Reduces glare and eye discomfort
- Increases personal safety from flying glass

Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible Light Transmitted	33%	18%	30%	18%
Total Solar Energy Rejected	65%	67%	61%	70%
UV Light Rejected	98%	98%	98%	98%
Glare Reduction	63%	64%	62%	60%
Visible Light Reflected	42%	16%	42%	18%
Shading Coefficient	0.40	0.38	0.45	0.34
Emissivity	0.68	0.68	0.68	0.68
U Value	0.97	0.97	0.47	0.47
Solar Heat Reduction	57%	45%	44%	38%

3M Building and Commercial Services Division

3M Center, Building 223-2S-24
St. Paul, MN 55144-1000

Printed in U.S.A. © 3M 2007 70-0709-0174-2 (37.5)ii